

Nexo – intelligent cordless nutrunners

Rexroth intelligent cordless nutrunners join wireless technology with all the advantages of the proven ErgoSpin hand-held nutrunner for all category A safety-critical tightening jobs in accordance with VDI 2862: Direct measurement of control and monitoring values and the storing of the fastening results for record keeping purposes.



- ▶ Fits easily into the existing infrastructure of any production environment
- ▶ Integrated controller
- ▶ Direct communication between the line PLC and the data collection server
- ▶ Protection class: IP40

Nexo cordless nutrunner

NXP pistolgrip nutrunner



- ▶ Working range 1.8–12 Nm
- ▶ Max. output drive speed 880 rpm
- ▶ Suitable for safety-critical tightening jobs in accordance with VDI/VDE 2862

FEATURES

- ▶ For troublefree working at hard-to-reach tightening positions
- ▶ Ergonomic design and maximum freedom of movement
- ▶ Graphic display: direct values of the tightening results, program selection, and process information
- ▶ Process reliability even without a connection to the WiFi network

Working range	Max. output drive speed	Tool mount	Weight without battery ¹	Installation length without battery ¹	Code	Order no.
Nm	rpm		kg	mm		
1.8–12	880	1/4" quick-change chuck	1.34	237	NXP012QD-36V	0608842005
1.8–12	880	1/4" quick-change chuck	1.34	237	NXP012QD-36V-B ²	0608842010

NOTE

Supply of Nexo cordless nutrunner without battery pack.
For slide-in battery pack see page 106.

¹ Weight of battery: 0.7 kg
Length of battery: 86 mm

² With integrated barcode scanner

Nexo cordless nutrunner

NXA right-angle nutrunner



- ▶ Working range 3–65 Nm
- ▶ Max. output drive 850 rpm
- ▶ Suitable for safety-critical tightening jobs in accordance with VDI/VDE 2862

FEATURES

- ▶ With slim angle head for high accessibility
- ▶ Graphic display: direct values of the tightening results, program selection, and process information
- ▶ Process reliability even without a connection to the WiFi network

Working range Nm	Max. output drive speed rpm	Tool mount	Weight without battery ¹ kg	Installation length without battery ¹ mm	Code	Order no.
3–11	850	3/8" square drive	1.56	442	NXA011S-36V	0608842011
3–11	850	3/8" square drive	1.56	442	NXA011S-36V-B ²	0608842012
3–15	600	3/8" square drive	1.56	442	NXA015S-36V	0608842001
3–15	600	3/8" square drive	1.56	442	NXA015S-36V-B ²	0608842006
6–30	310	3/8" square drive	1.99	534	NXA030S-36V	0608842002
6–30	310	3/8" square drive	1.99	534	NXA030S-36V-B ²	0608842007
10–50	185	3/8" square drive	2.03	534	NXA050S-36V	0608842003
10–50	185	3/8" square drive	2.03	534	NXA050S-36V-B ²	0608842008
13–65	135	3/8" square drive	2.03	534	NXA065S-36V	0608842013
13–65	135	3/8" square drive	2.03	534	NXA065S-36V-B ²	0608842014

¹ Weight of battery: 0.7 kg; length of battery: 86 mm

² With integrated barcode scanner

NOTE

Supply of Nexo cordless nutrunner without battery pack.
For slide-in battery pack see page 106.

Nexo cordless nutrunner

NXV VarioLine nutrunner



- ▶ Working range basic machine 1.8–12 Nm
- ▶ Working range with angle head 3–15 Nm
- ▶ Max. output drive of basic machine 880 rpm
- ▶ Max. output drive with angle head 600 rpm
- ▶ Suitable for safety-critical tightening jobs in accordance with VDI/VDE 2862

FEATURES

- ▶ With slim angle head for high accessibility
- ▶ Graphic display: direct values of the tightening results, program selection, and process information
- ▶ Process reliability even without a connection to the WiFi network

Working range Nm	Max. output drive speed rpm	Tool mount	Weight without battery ¹ kg	Installation length without battery ¹ mm	Code	Order no.
3–15/1.8–12 ²	600/880 ²	Basic machine with an output with thread and pin for the attachment of special output drives	1.56/1.35 ²	442	NXV012T-36V	0 608842 015
3–15/1.8–12 ²	600/880 ²		1.56/1.35 ²	442	NXV012T-36V-B ³	0 608842 016

¹ Weight of battery: 0.7 kg; length of battery: 86 mm

² Values without output drive

³ With integrated barcode scanner

NOTES

Supply of basic machine with angle head.
Supply of Nexo cordless nutrunner without battery pack.
For slide-in battery pack see page 106.

Nexo

Angle heads



Code	Suitable for	Tool mount	Weight kg	Max. torque* Nm	Gear ratio	Avg. efficiency	Order no.
NXAH11-15	NXA011S-36V/-B NXA015S-36V/-B	3/8" square drive	1.56	15	1.4	0.94	0 608 843 022
NXAH30	NXA030S-36V/-B	3/8" square drive	1.56	30	5.25	0.94	0 608 843 023
NXAH50-65	NXA050S-36V/-B NXA065S-36V/-B	3/8" square drive	1.56	65	6.363636	0.94	0 608 843 024

* Value refers to angle head

Nexo

Accessories and extensions



MOUNTING AID FOR ANGLE HEADS

Code	Suitable for	Order no.
ESWM	NXA030S-36V NXA050S-36V NXA065S-36V	3 608 876 473



PROTECTIVE CAP FOR ANGLE HEADS

Code	Suitable for	Quantity	Order no.
NXAPAH2	NXA030S-36V	5	0 608 843 015
	NXA050S-36V		
	NXA065S-36V		



PROTECTIVE CAP FOR ANGLE HEADS

Code	Suitable for	Quantity	Order no.
NXAPAH1	NXA011S-36V	5	0 608 843 016
	NXA015S-36V		



PROTECTIVE INSULATION FOR BATTERY ASSEMBLY

Code	Suitable for	Tool mount	Max. torque	Order no.
NXPP012	NXP12QD-36V	1/4" quick-change chuck	12 Nm	0 608 843 012



PROTECTIVE INSULATION FOR BATTERY ASSEMBLY

Code	Suitable for	Tool mount	Max. torque	Order no.
NXAP030	NXA030S-36V	3/8" square drive	30 Nm	0 608 843 011
	NXA050S-36V			
	NXA065S-36V			

Nexo – accessories and extensions



SLIDE-IN BATTERY PACK

Code	Quantity	Order no.
NX-BP2-36V	1	0608843019



SIMPLE CHARGER

Code	Voltage	Order no.
NX-BC36V	100V-240V (~50-60Hz)	0608843002

Battery charging cabinets for Rexroth slide-in battery packs on request



PROGRAMMING ADAPTER*

Code	Order no.
NX-A3	0608843021

* Adapter supplied without Ethernet cable



MICRO SD CARD

Code	Order no.
NX-SD	0608843005



HOLDER FOR RIGHT-ANGLE NUTRUNNERS

Code	Order no.
ESAT	3608876626

On request with sensors for tool detection



HOLDER FOR PISTOLGRIP NUTRUNNERS


Code	Order no.
NXPT	0608843008

Note: Cannot be used for pistolgrip nutrunners with protective insulation for battery assembly



TURNING SUSPENSION FOR RIGHT-ANGLE NUTRUNNERS

Code	Order no.
NXAMT	0608843003



SUSPENSION FOR PISTOLGRIP NUTRUNNERS

Code	Order no.
NXPB	0608843004

Nexo – accessories and extensions



EXTRA GRIP FOR PISTOLGRIP NUTRUNNERS

Code	Order no.
NXPH	0608843009

Note: Cannot be used for pistol-grip nutrunners with protective insulation for battery assembly.



ASSORTED COLORED RINGS

Code	Quantity	Order no.
NX-R	21 (3 pieces of each color)	0608843010



NEXO BRACKET FOR SUPPORT SYSTEMS (E. G. POSITIONING SENSORS)

Code	Quantity	Order no.
NX-HD	2	0608843018



ACCESS POINT*

Code	Order no.
NX-ACCESS	0608843007

* Without power supply unit.

Nexo

Browser-based operating software NEXO-OS

- ▶ Easy set-up as additional software installation is not necessary. Operating software can be used without local installation.
- ▶ Independence from end devices provides complete flexibility. Access to the browser-based software is not dependent on operating system nor end device.
- ▶ You can access the Nexo software by using any web-browser enabled device.
- ▶ Easy to learn, easy to use: Programming of individual tightening tasks is simple via the intuitive graphic user interface.
- ▶ Scalable user rights

